SONY
make.believe

LTX800G

Ideal for data-intensive backup and archiving in network and high-end servers, LTO4 provides a storage capacity of 800GB (native) and a transfer rate of 120MB/s (native).

- **Impressive storage capacity of up to 1.6TB compressed data (800GB native)**
- **Ultra fast data transfer rate of 120MB/s native and 240MB/s compressed**
- **Ideal to back up, restore and archive large applications**
- **High-speed access with 8KB LTO Cartridge Memory (LTO-CM) chip**
- **High reliability and durability**
- **Cleaning Tape: LTXCL**

Technical Specifications

Environmental requirements	
Operating Conditions (degrees F)	50~113
Operating Conditions (degrees C)	10~45
Operating Conditions (% RH)	10~80
Storage Conditions (degrees F)	60~90
Storage Conditions (degrees C)	16~32
Storage Conditions (% RH)	20~80
Record Transportation Conditions (degrees F)	-9~121
Record Transportation Conditions (degrees C)	-23~49
Record Transportation Conditions (% RH)	5~80

General Characteristics	
Recording density (Kftpi)	340
Magnetic material	Metal Particle
Native Recording Capacity (GB)	800
Compressed* Recording Capacity (TB)	1,6
Cartrige Width (mm)	105.4
Cartrige Height (mm)	102.5
Cartrige Depth (mm)	21.5
Weight with case (g)	275

Physical Characteristics	
Tape length (m)	820
Tape thickness (µm)	6.6
Tape width (mm)	12.65